

Product Data Sheet

250P

2" Commercial 20 Gauge Steel Door

HÖRMANN



2" commercial 250P doors are made of 20 gauge galvanized steel and comes with precisely designed tongue and groove section joints along with a double end stile design add to overall structural integrity.

- Tongue & groove section joints
- Available section heights: 21" & 24"
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- 14 gauge hinges, 11 ball bearing polymer rollers (3" track upgrade, 10 ball steel standard roller)
- Step plate, lift handle & pull rope included
- Bottom weather seal with aluminum retainer
- Double end stiles 16'3" and wider
- Inside slide lock included
- 10 year warranty on sections
- 1 year hardware warranty
- 1 year springs warranty

| Door Specification | Description |
|---|---|
| Standard Door Size | Width: 8' - 24'2" Height: 8' - 20' |
| Material Thickness / Door Type | Pan T&G 2" - 20 gauge - 0.032"nom. |
| Door Design | Deep Ribbed |
| Texture | Smooth |
| Colors | White |
| Galaxy Paint | N/A |
| Insulation | Non-insulated or insulated with Vinyl-back |
| Thermal Resistance (R-value) | 7.4 with optional insulation |
| Heat Transfer Coefficient (U-factor) | N/A |
| Air Infiltration Value (cfm/ft ²) | N/A |
| Door Sections Only (DSO) Option | YES |
| Springing | Torsion |
| Track Options | Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track |
| Builder's Grade | N/A |
| Window Options | 24" x 6", 24" x 12", Clear anodized full-view aluminum sections |
| Glass Options | Commercial Glass (annealed is standard): Clear, Satin Etch, White Laminate (Insulated Only) Full-view: Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey. Bronze, Mistlite, Black & White Laminate |
| Windload | Internal: W128, W129, W130, W131 |
| Hardware | 14 gauge hinges, 11 ball bearing polymer rollers, double end hinges over 16'2" & optional below |
| Strutting | 2 1/4" Strutting used up to 16'2" and 3" used after |
| Manufacturer Warranty | 10 year sections, 1 year hardware, 1 year springs |