

Product Data Sheet

255P

2" Commercial 25 Gauge Steel Door

HÖRMANN



2" commercial 255P doors are made of 25 gauge galvanized steel and comes with precisely designed tongue and groove section joints along with a double end stile design add to overall structural integrity.

- Tongue & groove section joints
- Available section heights: 21" & 24"
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- 14 gauge hinges, 11 ball bearing polymer rollers (3" track upgrade, 10 ball steel standard roller)
- Step plate, lift handle & pull rope included
- Bottom weather seal with aluminum retainer
- Double end stiles 16'3" and wider
- Inside slide lock included
- 10 year warranty on sections
- 1 year hardware warranty
- 1 year springs warranty

Door Specification	Description
Standard Door Size	Width: 8' - 20'2" Height: 8' - 20'
Material Thickness / Door Type	Pan T&G 2" - 25 gauge - 0.018"nom.
Door Design	Deep Ribbed & Short Raised
Texture	Woodgrain Stucco
Colors	White & Brown
Galaxy Paint	N/A
Insulation	Non-insulated or insulated with Vinyl-back
Thermal Resistance (R-value)	7.4 with optional insulation
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft²)	N/A
Door Sections Only (DSO) Option	YES
Springing	Torsion
Track Options	Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track
Builder's Grade	N/A
Window Options	24" x 6", 24" x 12", Clear anodized full-view aluminum sections
Glass Options	Commercial Glass (annealed is standard): Clear, Satin Etch, White Laminate (Insulated Only) Full-view: Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey. Bronze, Mistlite, Black & White Laminate
Windload	External: Z4500032 , Z4500039, Internal: W128, W129, W130, W131
Hardware	14 gauge hinges, 11 ball bearing polymer rollers, double end hinges over 16'2" & optional below
Strutting	2 ¼" Strutting used up to 16'2" and 3" used after
Manufacturer Warranty	10 year sections, 1 year hardware, 1 year springs