

Product Data Sheet

350S

Sandwich 2" Commercial Steel Door

HÖRMANN



2" commercial 350S door features a steel front and back with a polystyrene core and comes with precisely designed thermally broken section joints to reduce air infiltration and create a weather tight seal.

- Thermally broken tongue and groove section joints with thermal barrier joint seal
- Steel front and back 3-layer sandwich construction with polystyrene core
- R-Value: 10.4 (U-Factor: 0.21)
- Available section heights: 21" & 24"
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- 14 gauge hinges, 11 ball bearing polymer rollers (3" track upgrade, 10 ball steel standard roller)
- Step plate, lift handle & pull rope included
- Bottom weather seal with aluminum retainer
- Double end stiles 16'3" and wider
- Inside slide lock included
- 10 year warranty on sections
- 1 year hardware warranty
- 1 year springs warranty

| Door Specification | Description |
|--------------------------------------|--|
| Standard Door Size | Width: 8' - 24'2" Height: 8' - 20' |
| Material Thickness / Door Type | Sandwich T&G 2" - 0.015" |
| Door Design | Microgroove, Flush & Short Raised (Short-Raised unavailable for 16'9", 19'3" - 19'6", 19'9" - 19'11" but available up to 20' wide) |
| Texture | Woodgrain Stucco |
| Colors | White, Brown & Sandstone Tier II: Black, Silver Metallic |
| Galaxy Paint | N/A |
| Insulation | Polystyrene |
| Thermal Resistance (R-value) | 10.4 |
| Heat Transfer Coefficient (U-factor) | 0.21 |
| Air Infiltration Value (cfm/ft²) | N/A |
| Door Sections Only (DSO) Option | YES |
| Springing | Torsion |
| Track Options | Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track |
| Builder's Grade | N/A |
| Window Options | 24" x 6", 24" x 12", Clear anodized full-view aluminum sections |
| Glass Options | Commercial Glass (annealed is standard): Clear, Satin Etch, White Laminate Full-view: Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey. Bronze, Mistlite, White Laminate, Black Laminate |
| Windload | Internal:W120, W121, W122, W123 |
| Hardware | 14 gauge hinges, 11 ball bearing rollers |
| Strutting | 2 ¼" Strutting used up to 16'2" and 3" used after |
| Manufacturer Warranty | 10 year sections, 1 year hardware, 1 year springs |