

# Product Data Sheet



## 720A

1 3/4" Commercial Glazed Aluminum Sectional Door



720A offers 1 3/4" thick high quality glazing frames in anodized aluminum and comes with FingerGuard™ pinch-resistant section joints, which creates a deep tongue and groove fit for a tight seal.

- Pinch-resistant section joints interior and exterior
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- Between section weather seal
- Step plate, lift handle & pull rope included
- Fully enclosed aluminum rails
- Standard bottom weather seal
- Inside slide lock included
- 10 year warranty on sections (excludes glazing & aluminum sheet/panels)
- 1 year hardware warranty
- 1 year springs warranty

| Door Specification                   | Description  |
|--------------------------------------|--|
| Standard Door Size                   | Width: 8' - 20'2"<br>Height: 8' - 18'  |
| Material Thickness / Door Type       | Aluminum FPR<br>1 3/4" Commercial Glazed   |
| Door Design                          | Full-View Aluminum   |
| Texture                              | N/A  |
| Colors                               | Clear Anodized Aluminum  |
| Galaxy Paint                         | Optional   |
| Insulation                           | Aluminum Laminate or Polyurethane Insulated Steel Sections Available, Polystyrene insulation in rail with insulated glass                          |
| Thermal Resistance (R-value)         | Dependent on glass   |
| Heat Transfer Coefficient (U-factor) | Dependent on glass   |
| Air Infiltration Value (cfm/ft²)     | N/A  |
| Door Sections Only (DSO) Option      | N/A  |
| Springing                            | Torsion  |
| Track Options                        | Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track |
| Builder's Grade                      | N/A  |
| Window Options                       | Full-View Window   |
| Glass Options                        | Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey, Bronze, Mistlite  |
| Windload                             | N/A  |
| Hardware                             | 12 gauge hinges, 11 ball bearing, roller holder re-enforcement 16'2" and optional below  |
| Strutting                            | Refer to strut schedule  |
| Manufacturer Warranty                | 10 year sections (excludes glazing & aluminum sheet/panels), 1 year hardware, 1 year springs   |