Product Data Sheet

720A

1¾" Commercial Glazed Aluminum Sectional Door



720A offers 1¾" thick high quality grazing frames in anodized aluminum and comes with FingerGuard™ pinch-resistant section joints, which creates a deep tongue and groove fit for a tight seal.

- Pinch-resistant section joints interior and exterior
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- Between section weather seal
- Step plate, lift handle & pull rope included
- Fully enclosed aluminum rails
- Standard bottom weather seal
- Inside slide lock included
- 10 year warranty on sections (excludes glazing & aluminum sheet/ panels)
- 1 year hardware warranty
- 1 year springs warranty

Door Specification	Description
Standard Door Size	Width: 8' - 20'2'' Height: 8' - 18'
Material Thickness / Door Type	Aluminum FPR 1 ¾" Commercial Glazed
Door Design	Full-View Aluminum
Texture	N/A
Colors	Clear Anodized Aluminum
Galaxy Paint	Optional
Thermal Resistance (R-value)	Dependent on glass
Heat Transfer Coefficient (U-factor)	Dependent on glass
Air Infiltration Value (cfm/ft²)	N/A
Door Sections Only (DSO) Option	N/A
Springing	Torsion
Track Options	Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track
Builder's Grade	N/A
Window Options	Full-View Window
Glass Options	Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey. Bronze, Mistlite
Windload	90 MPH Standard (windload drawing and sticker available for purchase)
Hardware	12 gauge hinges, 11 ball bearing, roller holder re-enforcement 16'2" and optional below
Strutting	Refer to strut schedule
Manufacturer Warranty	10 year sections (excludes glazing & aluminum sheet/panels), 1 year hardware, 1 year springs

Hörmann Sectional Doors | 450 Airport Road | Sparta, TN 38583
1-877-897-7651 | info@hormann.us | hormann.us