

Product Data Sheet

720A

1¾" Commercial Glazed Aluminum Sectional Door

HÖRMANN



720A offers 1¾" thick high quality glazing frames in anodized aluminum and comes with FingerGuard™ pinch-resistant section joints, which creates a deep tongue and groove fit for a tight seal.

- Pinch-resistant section joints interior and exterior
- 15" radius bracket mount track standard (12" radius option in 2" track up to 14' high door only)
- Between section weather seal
- Step plate, lift handle & pull rope included
- Fully enclosed aluminum rails
- Standard bottom weather seal
- Inside slide lock included
- 10 year warranty on sections (excludes glazing & aluminum sheet/panels)
- 1 year hardware warranty
- 1 year springs warranty

Door Specification	Description
Standard Door Size	Width: 8' - 20'2" Height: 8' - 18'
Material Thickness / Door Type	Aluminum FPR 1 ¾" Commercial Glazed
Door Design	Full-View Aluminum
Texture	N/A
Colors	Clear Anodized Aluminum
Galaxy Paint	Optional
Thermal Resistance (R-value)	Dependent on glass
Heat Transfer Coefficient (U-factor)	Dependent on glass
Air Infiltration Value (cfm/ft²)	N/A
Door Sections Only (DSO) Option	N/A
Springing	Torsion
Track Options	Standard: 15" Radius Bracket Mount (12" radius option in 2" track up to 14' high door only) Bracket Mounted, Continuous Angle, Reverse Angle Track
Builder's Grade	N/A
Window Options	Full-View Window
Glass Options	Clear, Satin Etch, Gluechip, Obscure, Privacy, Grey, Bronze, Mistline
Windload	N/A
Hardware	12 gauge hinges, 11 ball bearing, roller holder re-enforcement 16'2" and optional below
Strutting	Refer to strut schedule
Manufacturer Warranty	10 year sections (excludes glazing & aluminum sheet/panels), 1 year hardware, 1 year springs