



SPEED-COMMANDER™ 1500 COMPACT

High-performance door

For interior applications - grocery, hospitals, retail, e-commerce and more

HÖRMANN

Speed-Commander™ 1500 Compact

Interior door with innovative tubular drive and aluminum guide tracks

Compact modern solution for retail, grocery and more

Thanks to anodized aluminum guide tracks and hood, integrated wiring and few visible screws, the SC 1500 Compact has a refined appearance that is well-suited for areas with customer facing traffic including grocery, retail and hospitals.

Compact aluminum guide tracks only require 5½" of clearance on either side of the door opening and a powerful UL rated tubular motor requires very little headroom clearance, enabling the SC 1500 Compact to fit into even the tightest spaces.

The door seals extremely well due to the narrow insertion area on the guide tracks where the panel runs inside, and guide track draft seals assist with forming a tight seal around the door panel. A fast opening speed of up to 6.5 feet per second (or 80 ips) greatly reduces the amount of air flow between workspaces.

A standard, full-width vision area provides maximum visibility, and a SoftEdge bottom profile automatically reverses the door upon accidental impact.

As standard, a light curtain is built into the guide tracks and monitors the closing zone of the door up to a height of 8'0", reversing the door if a light beam is interrupted. The risk of damage from a collision is greatly minimized.

For applications that require the control box to be remotely located, our optional remote keypad is the ideal accessory. All control functions are performed through a compact, 3" x 5½" keypad integral on either the left or right guide track. The same functions performable on the door control box may also be performed on the remote keypad including: initial installation set-up, opening and closing, as well as service and troubleshooting.




Stable panel
Welded panel with spring steel stiffener



Tight sealing
Narrow guide track panel insertion area and draft seals



Convenient remote keypad (optional)
Access control box functions when the control box is remotely installed



Powerful & compact UL tubular motor
Dependable operation for high-cycle applications



Warranty

Exclusive 2 year / 2.5 million cycle warranty

- 2.5 million cycles on motor / drive
- 2 years on all other components including the panel and control box

Equipment Features

Speed-Commander™ 1500 Compact

Door Type	SC 1500 Compact
Suitable Application	Interior
Size Range (ft)	
Maximum width x height with Soft Edge	13 x 16
Maximum width x height with Aluminum Edge	16 x 16
Operating Speeds (in/s)	
Maximum Opening	80
Closing Approximately	30
Panel	
Welded with Spring Steel Profile	●
Breakaway	
SoftEdge Rubber	●
Vision	
Full-width	●
Panel Colors	
Zinc Yellow (RAL 1018)	●
Pure Orange (RAL 2004)	●
Carmin Red (RAL 3002)	●
Gentian Blue (RAL 5010)	●
Agate Gray (RAL 7038)	●
Pure White (RAL 9010)	●
Guide Tracks (5½" x 4½" profile)	
6060 Anodized Aluminum	●
Hood	
Stainless Steel	●
Light Curtain Built into Tracks	●
Control Box	
Smart Start™ NXT NEMA 4X UL	●
3-phase, 208 V to 480 V (575 V w/transformer) 1-phase, 230 V	Available
Smart Start™ NXT HFCB NEMA 3 Non-UL 1-phase, 230 V only	Consult Factory
Emergency Opening	
Hand Crank for Emergency Opening	●
UPS Emergency battery pack Non-UL - Automatic door opening in case of power failure (With HFCB 1-phase control box only)	○

- = Standard
- = Optional
- = Unavailable

HÖRMANN NORTH AMERICA




Sparta, TN - North American Headquarters / Sectional Doors

SIX PRODUCTION PLANTS, ONE FAMILY

As one of the world's leading manufacturers of door systems, we're committed to providing the best quality, value, and selection. Whether residential, commercial or industrial, we have the solutions you're looking for. Each Hörmann product gives you the perfect array of benefits and options to satisfy your customers.



Puyallup, WA



Montgomery, IL



Oro-Medonte, ON Canada



Burgettstown, PA



Imperial, PA

USA

Toll Free: 800.365.3667
Email: info@hormann.us
Website: hormann.us

Canada

Toll Free: 866.792.9968
Email: info@hormann.ca
Website: hormann.ca

Mexico

Toll Free: 52 (81) 8308 7481
Email: info@hormann.com.mx
Website: hormann.mx



AVAILABLE FROM:



Follow us on social media



PN 27804727

We reserve the right to change specifications without notice. ©Hörmann (Issue 4.2026)