

Product Data Sheet

Deco Safe 5250

2" Recessed Panel Style Residential Steel Door



Deco Safe 5250 offers the beauty of recessed panel design and unsurpassed safety of our FingerGuard™ pinch-resistant joints.

- Numerous Recessed Panel Designs
- Pinch-resistant section joints interior and exterior
- 3-layer sandwich construction with polystyrene core bonded to steel front and back
- R-Value of 10.5
- Available section heights: 21" and 24" 18"(when required)
- Bracket mount 12" radius track
- Painted end caps
- Factory installed between section weather seal and side seal
- Limited lifetime warranty on sections
- 6 year hardware warranty
- 3 year torsion spring warranty

Door Specification	Description
Standard Door Size	Width: 8' - 18' Height: 6'6" - 10'6"
Material Thickness / Door Type	Sandwich Overall 2" Carriage Style FPR (Recess is 1 3/8")
Door Design	Longwood, Sorrento, Sanford & Davenport
Texture	Woodgrain
Colors	White & Sandstone
Galaxy Paint	Optional for both base door & overlay
Insulation	Polystyrene with steel backer
Thermal Resistance (R-value)	10.5
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft ²)	N/A
Door Sections Only (DSO) Option	N/A
Springing	Torsion/Extension
Track Options	Standard: Bracket Mount 15" Radius *10" Radius not available
Builder's Grade	N/A
Window Options	Full Row Lites with overlay options Non-insulated or Insulated
Glass Options	Double row of glass must be non-insulated Clear, Bronze, Satin Etch, Gluechip, Privacy, Mistlite, Obscure, Grey
Windload	Internal
Hardware	16 gauge hinges, 11 ball bearing rollers
Strutting	Refer to strut schedule
Manufacturer Warranty	Limited lifetime sections, 6 year hardware, 3 year springs