

Product Data Sheet

HÖRMANN

Style Safe 5200

2" Carriage House Style Residential Steel Door



Style Safe 5200 offers custom-designed beauty and unsurpassed safety, by pairing unique carriage house door styles with our FingerGuard™ pinch-resistant joints.

- Special carriage house designs
- Pinch-resistant section joints interior and exterior
- 3-layer sandwich construction with polystyrene core bonded to steel front and back
- R-Value of 10.5
- Available section heights: 28" & 32"
- Bracket mount 15" radius track
- Painted end caps
- Factory installed between section weather seal and side seal
- Woodgrain embossing
- Limited lifetime warranty on sections
- 6 year hardware warranty
- 3 year torsion spring warranty

Door Specification	Description
Standard Door Size	Width: 8' - 18' Height: 7' - 10'
Material Thickness / Door Type	Sandwich Overall 2" Carriage Style FPR (Recess is 1 3/8")
Door Design	0 (Base), 1 Stile, 2 Stile, A pattern, V pattern, 3 Stile & X pattern
Texture	Woodgrain
Colors	White
Galaxy Paint	Optional for both base door & overlay
Insulation	Polystyrene with steel backer
Thermal Resistance (R-value)	10.5
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft ²)	N/A
Door Sections Only (DSO) Option	N/A
Springing	Torsion/Extension
Track Options	Standard: Bracket Mount 15" Radius *10" Radius not available
Builder's Grade	N/A
Window Options	Full Row Lites with 1, 3, or 6 pane overlay Square or Arch Non-insulated or Insulated
Glass Options	Double row of glass must be non-insulated Clear, Bronze, Satin Etch, Gluechip, Privacy, Mistlite, Obscure, Grey
Windload	Internal
Hardware	16 gauge hinges, 11 ball bearing rollers
Strutting	Refer to strut schedule
Manufacturer Warranty	Limited lifetime sections, 6 year hardware, 3 year springs