

Product Data Sheet

Pro Safe 2100

2" Residential 25 Gauge (0.019" min.) Steel Door



The virtually no-maintenance Pro Safe 2100 doors are made of 25 gauge (.019" min.) galvanized steel and offers a wide range of styles and design options and pinch resistant section joints for added safety.

- Pinch-resistant section joints interior and exterior
- Available section heights: 18" & 21"
- 12" radius track (requires 12" of headroom)
- 15" radius optional (15" of headroom)
- Woodgrain embossing
- Factory installed between section weather seal and side seal
- Bonded full box center stiles and end stiles
- Bottom weather seal with aluminum retainer
- Limited lifetime warranty on sections
- 3 year hardware warranty
- 3 year torsion spring warranty

Door Specification	Description
Standard Door Size	Width: 6' - 20' Height: 6' - 16'
Material Thickness / Door Type	PAN FPR 2" - 25 gauge - 0.019" min.
Door Design	Short Raised, Long Raised, Country, Cottage, Medley
Texture	Woodgrain
Colors	Standard: White, Brown, Almond, Sandstone & Desert Tan Tier II: Teratone, Hunter Green, Black, Grey Timberlast: Golden Oak, Medium Oak, Walnut & Rosewood
Galaxy Paint	N/A
Insulation	Non-Insulated or Insulated with Polystyrene back
Thermal Resistance (R-value)	7.4 with optional insulation
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft ²)	N/A
Door Sections Only (DSO) Option	Yes
Springing	Torsion any height w/ extension up to 8' high in door height
Track Options	All track options
Builder's Grade	N/A
Window Options	Short/Long
Glass Options	Privacy, Grey, Bronze, Obscure, Glue Chip, Satin Etch, and Mistle
Windload	Yes
Hardware	16 gauge hardware and 11 ball bearing rollers
Strutting	2 ¼" Strutting used up to 16'2" and 3" used after
Manufacturer Warranty	Limited lifetime sections, 3 year hardware, 3 year springs