

Product Data Sheet

Pro Tech 2500

2" Residential 25 Gauge Steel Door

HÖRMANN



The virtually maintenance-free Pro Safe 2500 doors are made of 25 gauge galvanized steel and offers a wide range of styles and design options.

- Tongue & groove section joints
- Available section heights: 18" & 21"
- Insulation with vinyl backcover (7.4 R-Value)
- 12" radius track standard
15" radius track optional
- Woodgrain embossing
- Safety bottom fixtures
- 16 Gauge hinges, polymer rollers
- 14 gauge torsion tube shaft
- Back hang hardware included
- Aluminum retainer bottom seal
- Limited lifetime warranty on sections
- 2 year hardware warranty
- 3 year torsion spring warranty

Door Specification	Description
Standard Door Size	Width: 6' - 18' Height: 6' - 14'
Material Thickness / Door Type	PAN T&G 2" - 25 GA - 0.019"nom
Door Design	Short Raised, Long Raised, Country, Cottage, Medley, Shaker
Texture	Woodgrain
Colors	Standard: White, Brown, Almond, Sandstone & Desert Tan Tier II: Teratone, Hunter Green, Black Timberlast: Golden Oak, Medium Oak, Walnut & Rosewood
Galaxy Paint	N/A
Insulation	Non-Insulated or Insulated with Polystyrene back
Thermal Resistance (R-value)	7.4 with optional insulation
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft ²)	N/A
Door Sections Only (DSO) Option	Yes
Springing	Torsion any height w/ extension up to 8' high in door height
Track Options	All track options
Builder's Grade	Alternative Builder's options includes: 18 GA narrow-body hinges and hardware Black, bushing style rollers Plastic retainer and black astragal seal One spring counterbalance system through 16'x8' sizes
Window Options	Short/Long
Glass Options	Annealed Standard Privacy, Grey, Bronze, Obscure, Glue Chip, Satin Etch, and Mistlite
Windload	Yes
Hardware	16 gauge hardware, 11 ball bearing rollers, safety bottom brackets
Strutting	2 1/4" Strutting used up to 16'2" and 3" used after
Manufacturer Warranty	Limited lifetime sections, 2 year hardware, 3 year springs