

Product Data Sheet



Therma Safe 3200

Sandwich 2" Residential 25 Gauge (0.019" min.) Steel Door



The virtually maintenance-free Therma Safe features a steel front and back with a polystyrene core offers a wide range of styles and design options and pinch resistant section joints for added safety.

- Pinch-resistant section joints interior and exterior
- 3-layer sandwich construction with polystyrene core bonded to steel front and back
- R-Value of 10.5
- Available section heights: 18" & 21"
- 12" radius track (requires 12" of headroom)
15" radius optional (15" of headroom)
- Woodgrain embossing
- Painted end caps
- Factory installed between section weather seal and side seal
- Limited lifetime warranty on sections
- 4 year hardware warranty
- 3 year torsion spring warranty

Door Specification	Description
Standard Door Size	Width: 6' - 20' Height: 6' - 16'
Material Thickness / Door Type	Sandwich FPR 2" - 25 gauge - 0.019" min.
Door Design	Short Raised, Long Raised, Country, Cottage, Medley, Flush & Microgroove
Texture	Woodgrain Stucco - Microgroove
Colors	Standard: White, Brown, Almond, Sandstone & Desert Tan Tier II: Teratone, Hunter Green, Black, Grey Timberlast: Golden Oak, Medium Oak, Walnut & Rosewood
Galaxy Paint	Optional
Insulation	Sandwich polystyrene insulation with steel backer
Thermal Resistance (R-value)	10.5
Heat Transfer Coefficient (U-factor)	N/A
Air Infiltration Value (cfm/ft ²)	N/A
Door Sections Only (DSO) Option	Yes
Springing	Torsion any height w/ extension up to 8' high in door height
Track Options	All track options
Builder's Grade	N/A
Window Options	Short/Long Commercial windows only for MG
Glass Options	Privacy, Grey, Bronze, Obscure, Glue Chip, Satin Etch, and Mislite
Windload	Yes w/ Extreme Package Option
Hardware	16 gauge hardware and 11 ball bearing rollers
Strutting	2 1/4" Strutting used up to 16'2" and 3" used after
Manufacturer Warranty	Limited lifetime sections, 4 year hardware, 3 year springs